

MP 280 Lite

2" Mobile Thermal Receipt Printer



- Bluetooth Connectivity V4.0+USB
- Bluetooth pairing-Auto Reconnect
- Easy Paper Loading
- Light weight & Easy to Operate



Retail



Micro Finance



Parking lots



Field Force Automation



MP 280 Lite

2" Mobile Thermal Receipt Printer



Specification	MP 280 Lite
Print method	Direct thermal
Print speed	70mm/sec
Print resolution	203 dpi
Print width	up to 48mm
sensor	Paper end : reflective sensor
Media characteristics	
Media type	Receipt
Media Width	58mm
Media roll diameter	upto 40mm
Media thickness	60 to 100µm
Supply method	Easy paper loading
Physical characteristics	
Dimension	115mm*84mm*38mm
Weight	265g
Environmental characteristics	
Operating temperature	-10°C-50°C
Storage temperature	-20°C-60°C
Fonts/Graphics/Symbolises	
Character size	12*24 dot font
Character per line	24 characters/line 32 characters/line 42 characters/line
Character sets	Alpha-numeric : 95 Expanded graphics: 128*33 page
Instruction set	ESC/POS compatible



TVS ELECTRONICS LIMITED
www.tvs-e.in

For Sales Enquiry

☎ 044 6688 8822
✉ sales-support@tvs-e.in

For Service Enquiry

☎ 1860 425 2078
✉ support@tvs-e.in